



## TB20-C, bus coupler EtherCAT

### EtherCAT

- EtherCAT slave with Modular Device Profile (MDP) support
- Two EtherCAT ports (RJ45, 100BASE-TX)
- Up to 64 peripheral modules
- Modules can be replaced during operation (hot-swap)
- Automatic module I/O data mapping
- 1024 bytes of input data; 1024 bytes of output data
- 24 V DC power supply
- Integrated power supply unit for powering peripheral modules (2.5 A)
- Supplies the system's I/O voltage (24 V DC)
- 5 LEDs used as indicators for the current coupler, EtherCAT, and the link/activity status
- USB device port for online diagnostics, configuring parameters, setup, and firmware updates with "TB20 ToolBox"
- Can be alternatively configured, including its parameters, using the CoE protocol
- TB20 ToolBox simulation for setting up the I/O system without a higher-level controller in order to test the system's operation (I/O check)
- Concealed "factory reset" switch for restoring the module to its factory settings

The EtherCAT bus coupler makes it possible to access data from peripheral modules using the EtherCAT protocol. It can accommodate up to 64 modules of any kind connected in series with the bus coupler. It detects peripheral modules that are plugged in and can assign the corresponding I/O data to an EtherCAT mapping automatically. The EtherCAT bus coupler supports the Modular Device Profile. A large I/O image table size of 1,024 bytes makes it possible to implement comprehensive and complex systems. TB20 ToolBox can be used to easily configure the system and the various module parameters and transfer the corresponding settings to the coupler. Alternatively, the configuration can also be edited using the CoE object dictionary. Finally, running TB20 systems can be diagnosed in real-time and set up for testing purposes if an EtherCAT master is not yet connected (simulation / I/O check). A functioning TB20 configuration will always require a bus coupler and at least one peripheral module.

### Technical specifications

General information	
Order number	600-185-1AA11
Article name	TB20-C, EtherCAT bus coupler
Scope of delivery	Bus coupler EtherCAT, 24 V power supply connector, bus cover element, base module
Dimensions (DxWxH)	110 x 35 x 73 mm
Weight	Approx. 130 g
EtherCAT interface	
Number	2
Protocol	EtherCAT according to IEC standard 61158
Physical layer	Ethernet
Transmission rate	100 Mbps, full duplex
I/O image size	1024 bytes respectively
Connection	RJ-45
Features	Automatic process data configuration, Support of 'CANopen over EtherCAT' (CoE), Object directory according to 'Modular Device

	Profile' (MDP), Support of 'SDO Info' and 'Complete Access'
Diagnostic functions	cycle-current module diagnosis on the basis of module and channel status, subsequent module diagnosis on the basis of the diagnosis status in the object directory
<b>USB interface</b>	
Number	1
Protocol	Full-speed USB 1.1 device
Connection	Mini-USB
Isolation voltage	1.5 kV
Electrical isolation	Yes
<b>Number of modules that can be connected in series</b>	64
<b>Voltage supply</b>	24 V DC, 18...28 V DC
<b>Ambient conditions</b>	
Ambient temperature	0 °C ... +60 °C
Transport and storage temperature	-20 °C ... +80 °C
Relative air humidity	95 % r H without condensation
Pollution degree	2
Protection rating	IP 20
Certifications	CE, UL pending
<b>CE</b>	
Noise immunity	DIN EN 61000-6-2 "EMC Immunity"
Interference emission	DIN EN 61000-6-4 "EMC Emission"
Vibration and shock resistance	DIN EN 60068-2-8:2008 "Vibration" DIN EN 60068-27:2010 "Shock"
RoHS	Yes
REACH	Yes