



SmartClick HMI

Best cost-to-benefit ratio

	SC107	SC207	SC110	SC210
Display Size	7" Wide		10,1"	
Display Technology	TFT			
Display Colors	65.536			
Display Backlight	LED			
Display Resolution (pixel)	800 x 480		1024 x 600	
Backlight life (hours)	30 K			
Processor	ARM			
RAM	64 MB	32 MB	64 MB	
Flash	64 MB			
First Serial Port	Port 1 (RS232/RS485/ COM0)	Port 1 (RS232/485/MPI)	Port 1 (RS232/RS485/ COM0)	Port 1 (RS232/485/MPI)
Second Serial Port	Port 2 (RS232/RS485/ COM0)	-	Port 2 (RS232/RS485/COM0)	
USB Port Host	1 x v 1.1			
USB Port Device	1 x v 1.1			
Cardbus slot	1 x Secure Digital/MMC			
Ethernet	1 x 10/100 Mb			
Chassis	ABS Plastic			
Hardware Clock	Yes			
Clock battery	Battery (min.durability 5 yrs)		Supercapacitor 72h	
Power Supply (Vdc)	18 - 32			
Consumption (W)	5		8	
Operating Temperature (°C)	-10 ... + 50 (non condensing)			
Storage Temperature (°C)	-20 ... + 65			
Humidity	<85% (non condensing)			
External dimensions(W/H/D) (mm)	198,8 x 137,8 x 40,3	202 x 142 x 40	280 x 190 x 37,5	
Cut-out	190,2 x 129,2	194 x 134	271 x 181	



HMI

dimensions (W/H) (mm)			
Weight (kg)	~ 0,8	~ 1	~ 1,4
Protection degree (front)	IP 65		
Certifications	CE		