# **SIKO** | Product Overview





# Technical advancement and long-standing competence:

Today SIKO signifies more than five decades of experience in length, angle and speed metrology. The highest demands of our customers in both the industry and the mechanical engineering sectors result in the outstanding quality, precision and functionality of our products and services.

SIKO is certified to DIN EN ISO 9001: 2015. Careful handling of raw materials and resources is a matter of course.









Company Profile			
Pro	duct lines		
	PositionLine	Position indicators	6
	RotoLine	Rotary encoders	8
		Electronic displays	9
	LinearLine	Wire-actuated encoders	10
	DriveLine	Actuators	12
	MagLine	Magnetic length and angle	
		measurement systems	14
	SIKO Service feature		16
Service			18
Contact			19



# handwheel with an integrated analogue indicator.

Dr.-Ing. Günther Wandres founded SIKO GmbH.



Introduction of the first digital position indicator DA08. Today SIKO is the global market leader in the area of position indicators.



# 1980

A milestone on the way to a global market: establishment of the subsidiary SIKO Products in the USA.



ment technology; development of measurement indicators and the first electronic hollow-shaft



# 1991

Introduction of the first electronic position indicator

# 1992


Introduction of the magnetic measuring principle (MagLine) and wire-actuated encoders
(LinearLine).

#### Global success is no coincidence

The measuring technology from Buchenbach at the edge of the Black Forest is well represented around the world and throughout the stationary and mobile mechanical engineering sector.

Around 60 agencies ensure that our customers have access to direct contacts and technical support both at home and abroad.

The five successful subsidiaries in the United States, China, Singaour, Switzerland and Italy are the cornerstones of the global representation of SIKO GmbH.



The SIKO product portfolio encompasses five product ranges:

- Digital position indicators and hand wheels (PositionLine)
- Rotary encoders, geared potentiometers and measurement indicators (RotoLine)
- Wire-actuated encoders (LinearLine)
- Actuators (DriveLine)
- Magnetic measuring systems (MagLine)



# Direct contact to our product specialists

We are here for you and offer:

- Qualified, personal advice
- Global accessibility at sales subsidiaries and agencies
- Technical support
- International trade fair attendance
- Multi-lingual website with download area for the latest catalogues, data sheets, 3D design data and much more.

### Working for you

Around the world more than 200 SIKO employees are working for you today with a tremendous team spirit and in-depth know-how. All our committed teams are focused on "doing it better" with the ambition and passion they need to get it right. The constant, healthy growth of SIKO GmbH is truly a team effort.

### Visions for the future

Since 1990 Horst Wandres, a graduate industrial engineer and son of the company founder, has been leading the company with a vision for the future. In 2014, Mr Sven Wischnewski was appointed as a Member of the Management Board. Even today the company's course is being steadily plotted in Buchenbach for the coming decades.

#### 95

Introduction / development of the magnetic compact sensors.

#### 996

Introduction / development of magnetic, absolute length measurement.





2001
Debut of the new product family

2003 and 2005
On the way to key markets: Foundation of subsidiaries in Switzerland, Italy and China.



#### 2008

Introduction of bus-compatible position indicators for monitored format adjustment (APO4).





**2013**Foundation of the Singapur affiliate.

#### The human factor

At SIKO you will meet motivated employees who identify personally with the products that they manufacture. The necessary technical know-how and pride in one's own products are factors that should not be underestimated. SIKO also offers its workforce modern workplaces and a comprehensive package of fringe benefits. Promoting cross-departmental communication is also a main priority. Teamwork and the appreciation of each and every employee are fundamental values that are practised at SIKO every day. It is only possible to produce outstanding products of which even "the last 2 per cent" are accurate with this spirit.

# Production site Germany – an advantage we like to pass on

SIKO relies on streamlined, resourcesaving, high-tech production with prompt fulfillment of customers' wishes, thanks to well-coordinated, on-demand production mechanisms. In many sectors of industry, a high degree of automation can be found alongside specialized handwork.

SIKO GmbH is true to its tradition of manufacturing its products in Germany and Switzerland. Today and in the future we stand by our credo - Made in Germany/ Swiss made.

### **Quality features**

At SIKO continuous product optimisation is a natural phenomenon. Competence, state-of-the-art equipment and resources guarantee the highest possible quality:

- End-to-end 3D-CAD construction
- Rapid Prototyping
- In-house trials and test laboratories for long-term tests and material testing
- Use of computerised systems for simulation and collision tests
- Quality management in compliance with DIN EN ISO 9001





Modern, structured production sites in Germany and Switzerland

# **2014**Introduction of Ethernet drives "Industry4.0 -ready".

Mr Sven Wischnewski was appointed as a Member of the Management Board to support Mr Horst Wandres



**2015** First SIL2 magnetic sensor (MSA111C).



# **2016**Introduction of a new wire-actual ed encoderfor direct stroke measurement in hydraulic cylinders.





Top-Arbeitgeber 2017 Ausbildungsbetrieb 2017

2017
SIKO is honored as a top-ra employer and job training company.



#### 2019

Start of construction of the new production plant for electronic products in Bad Krozingen.

### **PositionLine**

SIKO is the inventor of the SIKO counter and the leading manufacturer in the mechanical-digital position indicator sector. The latest generation of SIKO programmable electronic indicators is a consistent further development of the versatile mechanical-digital position indicators and handwheels and also ensures an outstanding performance in bus-controlled applications.



Format change in packaging applications

# Electronic-digital position indicators

provide flexible, electronic capture of measured values and semi-automatic adjustment control at spindels.

#### **Benefits:**

- Display value, sense of rotation and decimal place are freely programmable
- Reset, incremental measurement, offset via keyboard
- Compatible with mechanical SIKO counters
- Bus-compatible for monitored format changes



#### Specifications

LCD indicators absolute

Battery-buffered

Programmable parameters

RS 485 bus interface, CANopen, Indusrial Ethernet













Ether CAT.









X,Y positioning



Tool positioning



End stop adjustment



Angle indicator



# Mechanical-digital position indicators

permit reliable numeric measured data indication and clear positioning of adjustment spindles.

#### Benefits:

- Low-cost, robust measurement system
- Easy hollow-shaft mounting
- Clear, precise digital display values thanks to integrated counter
- Individual gear ratios and displays

#### Specifications

Hollow shafts Ø 6 ... 35 mm

Metric or inch unit display

Mechanical detent/blocking

Selectable design (reading position)

Plastic or metal housing



#### **Control knobs**

are handy adjustment units with an integrated measurement system for variable mounting situations.

#### Benefits:

- Compact design
- Unit consisting of a handwheel and a position indicator
- Arbitrary mounting positions
- Analogue or digital display of measured values
- Special scales (analogue control knobs)
- Electronic or mechanical design

#### Specifications

Hollow shafts Ø 6 ... 20 mm Display integrated in the adjustment element Analogue and digital displays

Design (reading position) freely selectable



# Mechanical-analogue position indicators and handwheels

measure rotations via high-resolution analogue displays.

#### Benefits:

- Freely imprintable scales for flexible display of values
- Excellent reading quality thanks to large analogue scales
- Precise display of measurement values on a two-line display
- Angle display
- Robust handwheels made of metal or fibreglass-reinforced plastic

### Specifications

Handwheel Ø 56 ... 200 mm

Analogue display with scale

Optional with digital display

Corrosion and vibration-resistant, oil-filled

Metal or plastic handwheel












### **RotoLine**

SIKO has combined the "rotary encoder" family under the joint brand name Roto-Line. The comprehensive product know-how permits a versatile range of types that extends from inexpensive incremental rotary encoders of very varied design through to high-resolution absolute rotary encoders with fieldbus interfaces of industrial design or in robust heavy-duty housings.






### **Absolute rotary encoders**

register all motion precisely and absolutely. Motion is also detected and recorded in a de-energised state.

They are therefore the first choice for industrial and heavy-duty applications.





#### **Benefits:**

- Absolute measuring system
- Very high resolution
- Precise positioning
- Various interfaces
- Fieldbus interfaces
- Miniature designs
- Also available in heavy-duty housings

#### Magnetic, absolute rotary encoders

Hollow shafts up to Ø 15 mm
Solid shafts of Ø 6 ... 12 mm
Resolutions up to 4096 pulses/revolution (12 bit)
Resolution multiturn up to 8192 pulses/revolution (13 bit)

Output circuit: Analog, SSI, CANopen, CANopen redunant, CANopen Safety, fieldbus, Ethernet Up IP69K protection class



**Absolute rotary encoders** sense positions precisely and detect movements even in the currentless state.



**Incremental rotary encoders** sense speeds, velocities as well as distances and angles.





**Geared potentiometers** operate according to an absolute principle, making them suitable for level and distance as well as path, position and angle measurement (e. g.fire extinguising cannons or with gate control).

# Rotary encoders and geared potentiometers



### **Incremental rotary encoders**

are the simplest and most inexpensive solutions for measuring speeds, positions and angles.

#### Benefits:

- Optical and magnetic incremental rotary encoders
- High shock, vibration and temperature resistance
- Insensible e.g. to oils, lubricants, dirt, and water
- Wear- and maintenance-free sensor unit
- Universally usable: various hollow and solid shaft versions
- Compact design owing to highly integrated sensor unit
- High speeds up to 12000 rpm

#### Magnetic incremental encoders

Hollow shafts Ø 6 ... 28 mm

Solid shafts Ø 5 ... 12 mm

Resolutions up to 5000 pulses/revolution

Output circuits: PP, OP, LD5, LD24

Up to IP65 protection category



#### **Geared potentiometers**

are well known for their robust analogue technology. Measured values are recorded absolutely, which means there is no need for referencing.

#### Benefits:

- Long service life
- Optimized installation size
- Absolute measurement
- The encoder's analogue output signal can be used in a variety of ways
- Easy integration thanks to hollowshaft and solid-shaft technology
- Numerous gear ratios enable adaption to the customer's individual measuring range

#### **Geared potentiometers**

Hollow shafts Ø 14 ... 20 mm

Solid shafts Ø 6 ... 20 mm

Potentiometer output: current 4 ... 20 mA, voltage 0 ... 10 V

Up to IP68 protection category



### **Electronic displays**

SIKO electronic displays are multifunctional, electronic measurement solutions. They are ideal for simple indication of information on length and angles, speed, rotation or quantities.

#### Benefits:

- Easy adaptation to various sensor interfaces
- Freely programmable parameters
- Different operating voltages
- Good readability of the display unit
- Standardised designs for easy integration

#### Electronic displays

7 segment digit LED or LCD displays Operating voltages 24 V DC, 24 V AC, 110 V AC, 230 V AC


Counter inputs: PP 24 V signals, LD 5 V signals, serial SSI, number of pieces, speed and analogue 0 ... 10 V, 4 ... 20 mA External calibration or referencing possible Optional interfaces: RS232/RS485

Safe, redundant shaft encoders from SIKO help you to set up your complete system in accordance with standards.
The special safety shaft encoders from SIKO fulfill requirements up to Performance Level d!



# Successful measurement principles

The inner values of our measurement technology are the key to determining possible areas of application. SIKO's high-tech know-how of recording position values has resulted from decades of constant development.



Magnetic ring [1], sensor [2], digital signals [3]



# LinearLine

New technologies for discerning demands in the linear metrology sector. The result of decades of experience, the compact SIKO wire-actuated encoders are a reliable and easy to install option for linear position measurement. The possible range of applications is very wide, even under difficult ambient conditions.

#### Benefits:

- Temperature range up to -40 °C
- Robust and durable, even in wet, dirty conditions
- Easy wire run-out installation
- Flexible system integration of any output signals and interfaces
- Optional, enhanced safety due to a redundant sensor system

#### Specifications

Measurement lengths of 600 ... 15 000 mm

Output potentiometer: current 4 ... 20 mA,
voltage 0 ... 10 V

Interfaces: Inkremental, analog, SSI,
CANopen, CANopen redundant,
CANopen Safety, fieldbus, Ethernet
Robust plastic or metal housings
Various wire designs





Ensuring firm stance or determination of optimum work height – wire encoders are used for support adjustment and control of elevating platforms.



Wire-actuated encoders are the preferred solution in medical technology applications for adjusting the height or length of tomographs, operating tables, examination chairs and also x-ray equipment.



Wire-actuated encoders are ideal for integration when combined with car, truck and train lifting platforms. They are therefore also protected against environmental influences.



Integrated stroke and speed data acquisition for hydraulic cylinders. Designed for mechanical engineering or mobile machines.

# Wire-actuated encoders





Exact positioning of the operating table for fully-automatic adjustment with wire-actuated encoders requires maximum reliability and a compact design.



Robust and compact wire-actuated encoders for height adjustment and side positioning of the lifting fork of unmanned transport systems.



Open film



### **DriveLine**

"Short cycle times and changeover times, high productivity and quality with lower capital expenditure" is the recipe for success of ideal industrial processes.

The DriveLine actuators are particularly well suited for automatic format adjustment, stop positioning, tool alignment and valve adjustment as well as many other comparable positioning tasks – all of these tasks are easily mastered.

#### Benefits:

- Flexible machine concept, simple control behavior
- Low installation and mounting effort
- Highly available and maintenance-free
- Short cycle or retrofitting time
- High productivity and quality

#### DriveLine

Hollow shafts with diameters 10 ... 20 mm

Torques up to 14 Nm

Speeds up to 500 min<sup>-1</sup>

Magnetic multiturn encoder with resolutions up to 1600 pulses/revolutions

Interfaces: OP, LD5, LD24, Analog (R, U, I), Fieldbus and Industrial Ethernet













End stop adjustment



Angle adjustment



Indirect adjustment



Rotative adjustment









**More efficient axis adjustment:** The strength of DriveLine is its serial connection – centrally controlled, the SIKO actuators carry out their adjustment assignments synchronously.

Flexible and modular axis automation with DriveLine actuators makes it easy to achieve a long-term increase in both the machine efficiency as well as the product quality.

Adjustment with DriveLine actuators is around four times faster and much more accurate than with manual processes. Users speak of a boost in the production capacity of up to 50 percent.



DriveLine actuators ensure precise product position when on-the-fly production change is required.



Packaging machine manufacturers use DriveLine actuators in complex packaging machines with growing demands regarding version variety, productivity and accuracy.



**Direct positioning:**Direct action via axle or spindle. The principle of action corresponds to that of a compound table or of linear guides..



**Indirect positioning:** Indirect action (offset) on racks via cogwheel or worm gear.



Rotative adjustment: Direct action on the rotation axis or indirect action (offset) on a rotation axis via bevel gear or worm gear.



Open Film

# MagLine

The MagLine product line offers the possibility to replace measurement systems based on encoders with rack-and-pinion by a contactless system based on a magnetic principle.

MagLine is a versatile measuring solution with very flexible integration options, both incremental and absolute. Modern mechanical engineering applications profit in particular from the robust and economical measuring systems.

Key areas of application are measurement of linear and radial positions, angle values and rotational speed.

#### Benefits:

- Absolutely wear-free technology
- Insensitive to dust, chips, humidity, oils, fats, etc.
- Robust with shock and vibrations
- No measurement errors due to gear ratios or gear play
- High system accuracy and reproducibilty
- Easy handling and mounting
- Nearly maintenance-free

### **MagLine Micro**

This high-resolution feedback system is especially designed for precise, highly dynamic processes with special measurement requirements in the µm range, particularly in linear and rotative guidance and drive technologies as an alternative to optical systems.

#### **MagLine Micro**

Resolution max. 0.2 µm

System accuracy ±10 µm

Repeat accuracy  $\pm 1~\mu m$ 

Sensor-band gap max. 0.4 mm


Measurement lengths: up to max. 100 m

Freely selectable parameters










MagLine Micro: The sensor and the magnetic band of the measurement system are both perfectly



MagLine Micro detects length information in the  $\mu m$  range even in extremely dirty environments. It is typically used on linear drives.



In MagLine Basic, the magnetic band is also used as the system's measuring scale. The flexible design of the magnetic band allows it to be bent to a radius and used for simple angle measurement, e. q. with limit stop systems.



The small, compact band and sensor design allows integration of MagLine Macro in nearly every kind of linear guide system. Typical applications include storage technology.



Even when the magnetic band is completely covered with oil, Mag-Line Roto's measurement system still captures motor speed reliably and passes it on to the controls, for instance by way of motor feedback.

# Magnetic length, angle and speed measurement systems

# **MagLine Basic**

The application-proven, cleverly-devised Basic product series offers a particularly wide spectrum of components. An efficient solution for many individual applications, which fulfills all standard requirements of measurement precision in mechanical engineering or in the wood industry. Also available as a complete system with display and plug-and-play sensor!

#### MagLine Basic

Resolution max. 1 µm	
System accuracy ±25 μm	
Repeat accuracy ±5 μm	
Sensor-band gap max. 2 mm	
Measuring lengths up to max. 100 m	

Specially designed for very long measurement distances, MagLine Macro enables safe position detection with millimeter accuracy and interplay of many flexible units, particularly in storage or conveyor applications.

#### MagLine Macro

MagLine Macro

	Resolution max. 0.25 mm
	System accuracy ±1 mm
	Repeat accuracy ±1 mm
	Sensor-band gap max. 20 mm
	Measuring lengths up to max. 160 m

# **MagLine Roto**

The Roto Series is the ideal alternative to conventional optical encoder systems – especially for exact revolution or angle measurement under extreme conditions such as oil baths (e.g. on round tables).

#### MagLine Roto

Hageme Roto		
yp. resolution up to 200 000 pulses/revolution		
System accuracy ±0.5°		
Repeat accuracy ±1 increment Sensor-band gap max. 2 mm		











Magnetic measurement technology in a customized solution: Closed-loop, electronic length stop with circular saws.



MagLine senses magnetic fields contactlessly and converts the periodic signals received into analogue or digital values. The direct, contactless measurement principle prevents mechanical influences affecting the measurement result and allows simple integration in mechanical engineering situations.





### Retrofit

Boost efficiency! Reduce tooling times! The SIKO Retrofit division works in line with these aims. SIKO Retrofit offers a full retrofitting system for existing plants for monitored format adjustment - all from one source.

The system flexibly adapts to the needs of the respective plant, whether the application requires electronic position indicators for spindle or slide positioning or if actuators are used for fully-automatic positioning of spindles.

Simply plug and play! The user interface developed especially for format changes is intuitive and easy to use.

Our product specialists are at your disposal to work out the best solution for upgrading your machine.

We are at your side to provide support with applications, examples and technical documentation. For these services we use control units and components of renowned manufacturers such as Siemens, Rockwell Automation, BECKHOFF, B&R and HMS. For networking we use conventional industrial Ethernet or standard field bus interfaces such as Ethernet/IP, Profinet, EtherCAT and POWERLINK or PROFIBUS-DP, CANopen etc.



#### **Benefits:**

- Higher machine efficiency owing to reduced downtimes
- Operative user interface enables quick commissioning
- Higher process safety thanks to monitored change of format
- Flexibly configurable system
- Turnkey system, completely from one source







Retrofitting of existing systems which previously contained manual wheels or mechanical position indicators.



Monitored format adjustment on spindles with electronic position indicators.



Monitored format adjustment on slide adjustment features with electronic position indicators.




Full automation of spindles and machines by means of actuators.

# Higher performance through retrofitting - products and service

State-of-the art technological components for modernizing or upgrading plants and machines. Our service offers optimum design as well as turnkey integration for controls, sensors, position indicators, and positioning drives.

# Innovative system solutions with know-how

Alongside its comprehensive portfolio in the measurement and control technology field, SIKO is also a system supplier of customized overall solutions. Our engineering services are part of this allround and yet tailored approach for your respective assignment.



# Creating engineering solutions – also at your premises

Our experts would be pleased to assess your systems at your premises and work with you to draw up suitable solution proposals. We analyze the special circumstances of each individual project to find perfectly tailored solutions. We focus on your needs.

We supply everything from one source, starting with engineering, installation and commissioning, through to aftersales service and technical support: SIKO is the right contact for you.

Take advantage of our consultation services for using different versions of new products!

#### Your advantages

- SIKO as a central contact that provides a technical overall solution for you
- You profit from the comprehensive SIKO know-how acquired over decades
- A flexible, tailored solution, fully geared to your individual requirements
- SIKO's own comprehensive measuring and automation technology product portfolio



Simple retrofitting of existing systems: The efficiency of existing systems can be improved considerably, down times are minimized and off-spec products prevented.



We collaborate with our powerful cooperation partners to optimise all relevant system aspects such as efficiency, availability and operational safety. Our range of optional services includes analysis, installation, commissioning, training, service and maintenance.

# Sales / personal contact

Our sales team and our international sales partners would be pleased to answer your enquiries. Contact us at Tel. +49 7661 394-0

### Website with download area

PDF data and program routines for our programmable devices are available via the SIKO Homepage.

At www.siko-global.com you can find:

- Data sheets
- Catalogues
- Installation Instructions
- Manuals
- Configuration files
- 3D design files
- Product films
- Sales partners directory

## **Technical support**

Our technical support team provides assistance and first-hand information.

Tel. +49 7661 394-457

E-Mail: support@siko-global.com

#### SIKO at Youtube

In our SIKO Youtube channel you will find helpful tutorials, expert videos or insider tips for our products.

www.youtube.com/sikoglobal







#### Advantages are:

- Native and neutral data formats, suitable for your CAD system
- Preview function and direct download
- Full-text search
- 24 h access to product catalogue
- Versatile display options
- Free service

### 3D models for mechanical engineering

We offer constructors true-to-size, reduced-detail 3D data via the Cadenas platform. This allows configuration of attributes which define the contours of the SIKO device. After registering via our product pages on the internet, there is 24-hour online access to this service: www.siko-global.com

# Cadenas PARTcommunity ...

# Do you want to contact an agency near you?

Visit or website www.siko-global.com, and go to the "Contact" menu item to access all the latest contact data of our agencies.

Africa
South Africa
Asia
Canada
China
India
Indonesia
Iraq
Iran
Israel
Japan
Malaysia
Singapore
South Korea
Taiwan
Thailand
United Arab Emirates
Vietnam
Australia

Australia New Zealand

Europe
Austria
Belarus
Belgium
Bulgaria
Croatia
Cyprus
Czech Republic
Denmark
Estonia
Finland
France
Germany
Great Britain
Greece
Hungary
Italy
Latvia
Liechtenstein
Lithuania
Luxembourg
Montenegro
Netherlands
Norway
Poland
Portugal
Romania
Russia
Serbia
Slovakia
Slovenia
Spain
Sweden
Switzerland
Turkey
Ukraine

America	
Argentina	
Brazil	
Canada	
Ecuador	
Mexico	
USA	



**Production: Germany and Switzerland Sales: World wide** 



## Headquarters:

SIKO GmbH

Weihermattenweg 2 D-79256 Buchenbach

## Phone

+49 7661 394-0

#### Fax

+49 7661 394-388

### E-Mail

info@siko-global.com

### Subsidiaries:

- SIKO Products Inc
- SIKO Italia S.r.l.
- SIKO Magline AG
- SIKO International Trading (Shanghai) CO., Ltd.
- SIKO Products Asia Pte. Ltd.

# www.siko-global.com

Stay up to date! Follow us at "SIKO-global"















